



Underlayment - Black Muffler

TECHNICAL SPECIFICATIONS

DESCRIPTION

Underlayment

SIZE

Coverage Area	BLACK MUFFLER A: 200 sq. ft./roll, BLACK MUFFLER B: 100 sq. ft./roll
Product Width	47.2"
Product Length	BLACK MUFFLER A: 50.9", BLACK MUFFLER B: 25.4"
Product Thickness (mm)	2.5 mm (0.098")

DETAILS

Features	Sound Barrier: exceptional noise protection Moisture Barrier: effective built-in moisture barrier with additional barrier film Ease of Install: reducing prep for less-perfect subfloor
Product Type	Roll
Indoor/Outdoor	Indoor Only
Installation Type	Self Adhesive Overlap Lip & Tape
Material	Closed-cell polyethylene foam laminated to 3 mil polyethylene film
Color	Black foam on silver film
Suitable for products	WPC, SPC, Laminate and Engineered Wood Floor

WARRANTY

Residential Warranty	Limited Lifetime
Commercial Warranty	Limited Lifetime

CERTIFICATION

FloorScore	Certified
------------	-----------

PERFORMANCE

	Test Standard	Requirement	Result
Impact Sound Insulation Class (IIC)	ASTM E492 & E989	-	72 dB
Delta Impact Sound Isolation Class (ΔIIC)	ASTM E2179	-	25 dB
Airborne Sound Transmission Loss Class (STC)	ASTM E90 & E413	-	73 dB
Compressive Strength @ 25%	ASTM D3575	-	≥ 11 psi
VOC Emission	CA 01350	OEHHA RELs	FloorScore Certified
Formaldehyde Emission	CA 01350	≤ 9 µg/m ³	Not detected

PACKAGING

	BLACK MUFFLER A	BLACK MUFFLER B
Sq. ft./Roll	200 sq. ft.	100 sq. ft.
Lb/Roll	9.24 lb (4.20 kg)	4.62 lb (2.10 kg)
Rolls/Box	4 roll/box	6 roll/box
Sq. ft./Box	800 sq. ft.	600 sq. ft.
Sq. ft./Pallet	3200 sq. ft.	3600 sq. ft.